





MAIN SEA CONTAINER TYPES

20 FEET DC - DRY CARGO CONTAINER (20'X8'X8'6")*					
	WEIGHTS	Tare	Max. Payload		
		2210-2400 kg (4875-5290 lbs)	21700-28240 kg (47850-62270 lbs)		
	MEASUREMENTS	external	internal	door opening	
		length	6058 mm (20')	5900 mm (19'4")	-
		width	2438 mm (8')	2345 mm (7'8")	2335 mm (7'8")
	height	2591 mm (8'6")	2400 mm (7'10")	2290 mm (7'6")	
CUBIC CAPACITY	33.3 m3 (1175 cft)				

40 FEET DC - DRY CARGO CONTAINER (40'x8'x8'6")*					
	WEIGHTS	Tare	Max. Payload		
		3630-3740 kg (8005-8245 lbs)	26740-26850 kg (58960-59205 lbs)		
	MEASUREMENTS	external	internal	door opening	
		length	12192 mm (40')	12030 mm (39'6")	-
		width	2438 mm (8')	2345 mm (7'8")	2335 mm (7'8")
	height	2591 mm (8'6")	2400 mm (7'10")	2290 mm (7'6")	
CUBIC CAPACITY	67.7 m3 (2390 cft)				

40 FEET HIGH CUBE - DRY CARGO CONTAINER (40'X8'X9'6")*					
	WEIGHTS	Tare	Max. Payload		
		3880-3900 kg (8555-8600 lbs)	26580-26600 kg (58610-58655 lbs)		
	MEASUREMENTS	external	internal	door opening	
		length	12192 mm (40')	12030 mm (39'6")	-
		width	2438 mm (8')	2350 mm (7'8")	2335 mm (7'8")
	height	2896 mm (9'6")	2710 mm (8'11")	2595 mm (8'6")	
CUBIC CAPACITY	76.5 m3 (2700 cft)				


20 FEET FLAT RACK - FLAT RACK CONTAINER (20'X8'X8'6")*					
	WEIGHTS	Tare	Max. Payload		
		2350-2500 kg (4760-5510 lbs)	17850-30150 kg (39360-66480 lbs)		
	MEASUREMENTS	external	internal		
		length	6058 mm (20')	length between end walls 5900 mm (19'4")	side opening 5530-5700 mm (18'2"-18'8")
		width	2438 mm (8')	width load-bed overall 2400 mm (7'10")	width between side rail stanchions 2230-2250 mm (7'4"-7'5")
	height	2591 mm (8'6")	2270-2285 mm (7'5"-7'6")		

***DIMENSIONS AND WEIGHTS ARE MERELY ORIENTATIVE**


*If your cargo may exceed space limits (internal or roof, or door opening), please consult our Team.

MAIN SEA CONTAINER TYPES


40 FEET FLAT RACK - FLAT RACK CONTAINER (40'X8'X8'6")*

	WEIGHTS	Tare	Max. Payload		
		4900 kg (10805 lbs)	40100 kg (88420 lbs)		
	MEASUREMENTS	external	internal		
		length	12192 mm (40')	length between end walls 12150 mm (39'10")	side opening 11835 mm (38'10")
		width	2438 mm (8')	width load-bed overall 2400 mm (7'10")	width between side rail stanchions 2230-2240 mm (7'4")
height	2591 mm (8'6")	2035 mm (6'8")			


20 FEET OPEN TOP - OPEN TOP CONTAINER (20'X8'X8'6")*

	WEIGHTS	Tare	Max. Payload			
		2230-2250 kg (4915-4960 lbs)	21770-28230 kg (48005-62245 lbs)			
	MEASUREMENTS	external	internal	door opening	roof opening	
		length	6058 mm (20")	5900 mm (19'4")	-	5740-5760 mm (18'10"-18'11")
		width	2438 mm (8')	2330-2340 mm (7'8")	2330 mm (7'8")	2190-2210 mm (7'2"-7'3")
height	2591 mm (8'6")	2380 mm (7'10")	2220-2255 mm (7'3"-7'5")	-		
CUBIC CAPACITY	31.8-32.9 m3 (1125-1160 cft)					

40 FEET OPEN TOP - OPEN TOP CONTAINER (40'X8'X8'6")*

	WEIGHTS	Tare	Max. Payload			
		3650 kg (8050 lbs)	26830 kg (59160 lbs)			
	MEASUREMENTS	external	internal	door opening	roof opening	
		length	12192 mm (40")	12045 mm (39'6")	-	11890 mm (39')
		width	2438 mm (8')	2340 mm (7'8")	2335 mm (7'8")	2185-2210 mm (7'2"-7'3")
height	2591 mm (8'6")	2380 mm (7'10")	2255 mm (7'5")	-		
CUBIC CAPACITY	67.1 m3 (2370 cft)					

20 FEET REEFER - REEFER CONTAINER (20'X8'X8'6")*

	WEIGHTS	Tare	Max. Payload			
		2850-3500 kg (6285-7715 lbs)	17090-27280 kg (37685-60150 lbs)			
	MEASUREMENTS	external	internal	door opening		
		length	6058 mm (20')	5480-5500 mm (17'11"-18')	-	
		width	2438 mm (8')	2230-2285 mm (7'4"-7'6")	2165-2285 mm (7'1"-7'6")	
	height	2591 mm (8'6")	2135-2255 mm (7'-7'5")	2160-2210 mm (7'-7'3")		
	CUBIC CAPACITY	26.2-28.3 m3 (925-1000 cft)				
VOLTAGE	180/220V and 380/440V, 50/60Hz, 3-phase					
TEMP. RANGE	-25/+25 C					

***DIMENSIONS AND WEIGHTS ARE MERELY ORIENTATIVE**

*If your cargo may exceed space limits (internal or roof, or door opening), please consult our Team.


E2E LOGISTICS SOLUTIONS SL

C/Rambla de Catalunya, 5 Pral. 3ª 08007 (Barcelona) Spain


Tel: 34 931596600 Fax: 34 931596888 Website: www.e2elogistics.es



40 FEET REEFER - REEFER CONTAINER (40'X8'X8'6")*

	WEIGHTS	Tare	Max. Payload			
		4500-5400 kg (9920-11905 lbs)	25080-25980 kg (55300-57285 lbs)			
	MEASUREMENTS	external	internal	door opening		
		length	12192 mm (40')	11235-11575 mm (36'10"-38')	-	
		width	2438 mm (8')	2240-2285 mm (7'4"-7'5")	2240-2280 mm (7'4"-7'6")	
		height	2591 mm (8'6")	2175-2250 mm (7'2"-7'5")	2200 mm (7'3")	
	CUBIC CAPACITY	57.5-58.7 m3 (2030-2075 cft)				
	VOLTAGE	380/440V, 50/60Hz, 3-phase				
TEMP. RANGE	-25/+25 C					

40 FEET REEFER HIGH CUBE- REEFER CONTAINER (40'X8'X9'6")*

	WEIGHTS	Tare	Max. Payload			
		4700-5200 kg (10365-11465 lbs)	25780-29250 kg (56845-64495 lbs)			
	MEASUREMENTS	external	internal	door opening		
		length	12192 mm (40')	11575 mm (38')	-	
		width	2438 mm (8')	2280-2290 mm (7'6")	2280-2290 mm (7'6")	
		height	2895 mm (9'6")	2525-2550 mm (8'3"-8'4")	2435 mm (8')	
	CUBIC CAPACITY	66.7-68 m3 (2355-2400 cft)				
	VOLTAGE	380/440V, 50/60Hz, 3-phase				
TEMP. RANGE	-25/+25 C					

***DIMENSIONS AND WEIGHTS ARE MERELY ORIENTATIVE**

*If your cargo may exceed space limits (internal or roof, or door opening), please consult our Team.



Big enough to handle, small enough to care
YOUR BEST PARTNER IN SPAIN

E2E LOGISTICS SOLUTIONS SL

C/Rambla de Catalunya, 5 Pral. 3ª 08007 (Barcelona) Spain

Tel: 34 931596600 Fax: 34 931596888 Website: www.e2elogistics.es

